



SECURITY DEVICES INTERNATIONAL

Byrna Technologies inc. 100 Burtt Road, Suite 115 Andover, MA 01810-5915

| (978) 868-5011 | (905) 582-6402

www.securitydii.com | info@securitydii.com

CS SPECIFICATIONS SHEET 40MM LESS-LETHAL AMMUNITION

OPERATIONAL & SHIPPING SPECIFICATIONS




| | |
|--------------------------|--|
| Description | BIP CS Powder (CS), Cartridge, 40mm |
| Model Number | S-1080 CS |
| Type | Blunt impact kinetic energy round with collapsible head |
| Compatibility | All 40mm Launchers |
| Operational Range | 5 – 262 feet (1.5 –80 meters) |
| Cartridge Material | Glass Filled Nylon |
| Diameter | 1.57 in (40mm) |
| Length | 3.98 in (101mm) |
| Weight | 1.77 oz (50.3g) |
| Muzzle Velocity | 290 feet/second (88.4 meters/second) |
| Kinetic Energy at Muzzle | 208 J (153 ft•lb) |
| UN Number | 0012 |
| Hazard Class | 1.4 S |
| Quantity per Box | 25 |
| Deployment | It is stressed that shot placement is critical. Shots to the head, neck, thorax, heart, or spine can result in fatal or serious injury. <i>As a result, SDI recommends shooters target areas according to their agency's use of force model.</i> |

Safe deployment distance: 5 feet / 1.5m
 Optimum firing distance: up to 40m
 Maximum effective firing distance: up to 60m
 Operating temperatures: -25c to 66c

Warranty: 5 years from date of manufacture

All specifications are standard and are subject to change without notice.



MADE IN AMERICA