



SECURITY DEVICES INTERNATIONAL

Byrna Technologies inc. 100 Burtt Road, Suite 115 Andover, MA 01810-5915

| (978) 868-5011 | (905) 582-6402

www.securitydii.com | info@securitydii.com

MO SPECIFICATIONS SHEET 40MM LESS-LETHAL AMMUNITION

OPERATIONAL & SHIPPING SPECIFICATIONS




Description	BIP Malodorant (MO), Cartridge, 40mm
Model Number	S-1040 MO
Type	Blunt impact kinetic energy round with collapsible head
Compatibility	All 40mm Launchers
Operational Range	5– 262 feet (1.5 –80 meters)
Cartridge Material	Glass Filled Nylon
Diameter	1.57 in (40mm)
Length	3.98 in (101mm)
Weight	1.77 oz (50.3g)
Muzzle Velocity	290 feet/second (88.4 meters/second)
kinetic Energy at Muzzle	208 J (153 ft•lb)
UN Number	0012
Hazard Class	1.4 S
Quantity per Box	25
Deployment	It is stressed that shot placement is critical. Shots to the head, neck, thorax, heart, or spine can result in fatal or serious injury. As a result, SDI recommends shooters target areas according to their agency's use of force model.

Safe deployment distance: 5 feet / 1.5m
 Optimum firing distance: up to 40m
 Maximum effective firing distance: up to 60m
 Operating temperatures: -25c to 66c

Warranty: 5 years from date of manufacture

All specifications are standard and are subject to change without notice.



MADE IN AMERICA